

Power Cord IEC 320 2m  
9146340620

Desktop Power supply  
100-240V AC to 24V DC  
4524001000 - 5m cord  
4524001002 - 15m cord

DIN rail Power supply  
100-240V AC to 24V DC 10A  
7519020435 (max. 16 bars)

DIN rail Power supply  
100-240V AC to 24V DC 4A  
7519020425 (max. 5 bars)

DIN rail Power supply (UL)  
100-240V AC to 24V DC 3, 3A  
7519020430 (max. 5 bars)

Connector device M12 female angled  
5 pole (screw connections)  
7519020355 - Ø4-6 mm cables  
7519020356 - Ø6-8 mm cables  
Connector device M12 female straight  
5 pole (screw connections)  
7519020350 - Ø4-6 mm cables  
7519020351 - Ø6-8 mm cables

Status Module  
Performax (IQ) Easy EX  
4530000300

Cord device M12 female angled 5 pole  
7519020375 - 5 m, unshielded  
7519020376 - 10 m, unshielded

Cord device M12 female straight 5 pole  
7519020365 - 5 m, unshielded  
7519020366 - 10 m, unshielded

Protective hose ATEX  
9380531320 per m

Hose clip ATEX  
9250101013 needed 4 pieces /m hose

Fitting ATEX  
9370521017



ATEX ZONE

NON-ATEX ZONE

**Ex Certified Product**  
No modifications permitted without the approval of the "authorised person"

Remark:

- The Status Module Performax (IQ) Easy EX has one connection for a bar

 An ITW Company www.simco-ion.nl Tel: +31 (0)573 288333	Name: Performax Easy EX (Speed) system overview				Drawn: RJ	Part no.: —
	CAD generated NOT updated	Dimensions in mm	Date: 2-2-2017	A3 M: 1:1	 ECN-	Check: <i>AB</i>